

Protective fleece, breathable

UZIN PFB BLUE

Self-adhesive and diffusion-open cover fleece

MAIN APPLICATION FIELD:

- ▶ Covering and protecting sealed or oiled parquet floors
- ▶ Covering and protecting commercial floors, e.g. resilient and textile floor coverings, laminate, tile and natural stone coverings
- ▶ Covering and protecting shower trays and bathtubs, kitchen worktops, sanitary facilities and stairs

SUITABLE ON / FOR:

- ▶ Sealed or oiled wood flooring
- ▶ Laminate flooring
- ▶ All common resilient coverings
- ▶ Short-pile or looped textile coverings
- ▶ Needle felt coverings
- ▶ Ball yarn
- ▶ Tile and natural stone coverings
- ▶ stairs
- ▶ Shower trays and bathtubs
- ▶ Kitchen and work surfaces
- ▶ Ceramics, sanitary facilities



PRODUCT BENEFITS/FEATURES:

UZIN PFB BLUE is a reusable, self-adhesive and diffusion-open protective fleece for floors and surfaces and is used for professional protection during renovation work. The protective fleece is particularly suitable for freshly laid, sealed or oiled parquet floors. Thanks to the special anti-slip coating, the product adheres securely to the floor and can be easily removed without leaving any residue. The waterproof surface protects surfaces from liquids, is easy to clean and does not shed. For indoor use.

- ▶ Open to diffusion
- ▶ Can be used multiple times
- ▶ Good fixation on the substrate, reduces risk of falling, prevents slipping
- ▶ Impermeable to moisture
- ▶ Washable, easy to clean
- ▶ Can be removed without leaving any residue



TECHNICAL DATA:

Packaging	Roll
Pack size	50 m ²
Material type	Fleece: 100% polyester
Color	blue
Area weight	160 g/m ²
Thickness	2,5 mm
Water vapor permeability	70 g/m ² / 24 h*
Length	50 m
Width	1 m

* according to ASTM E-96/2005

SUBSTRATE PREPARATION:

The substrate should be dry, clean, smooth and as free of dust as possible to ensure optimum adhesion and repeated use. Dust and dirt on the surface to be protected can impair the adhesive strength and negatively affect the reusability of UZIN PFB BLUE, as well as possibly causing damage to the surface.

APPLICATION:

- ▶ Roll out UZIN PFB BLUE, adhesive side down and apply firmly to the substrate by rubbing, brief loading or walking on.
- ▶ Depending on the area of application, UZIN PFB BLUE can be laid either butt-jointed or with overlapping joints.
- ▶ Before removing UZIN PFB BLUE, clean the protective fleece either by vacuuming or wiping and allow to dry.
- ▶ Roll up UZIN PFB BLUE for reuse with the adhesive side facing inwards.

IMPORTANT NOTES:

- ▶ The cleaner the surface to be protected is before covering, the more often UZIN PFB BLUE can be reused. Any dust and dirt can adhere to the fleece surface and reduce adhesion.
- ▶ Immediately absorb any spilt liquids on the protective fleece. Special care must be taken to ensure that no liquid penetrates into the joint or edge area below the fleece. This could irreversibly damage sensitive substrates, such as parquet floors, to the point of complete destruction.
- ▶ UZIN PFB BLUE is not cut-resistant. Do not cut on the masking fleece or lay a cut-resistant underlay beforehand.
- ▶ UZIN PFB BLUE may be used for a maximum of 3 months at a time.
- ▶ The permissible duration of use of UZIN PFB BLUE on the substrate to be protected varies depending on the type of floor covering. We recommend regularly checking the compatibility at various points during use.
- ▶ Partial covering of surfaces can lead to colour changes, depending on the type of substrate and the influence of light. To avoid this, it is recommended that floor coverings are always completely covered.
- ▶ To avoid damage to the covering surface, it is essential that dirt, grains of sand or other foreign substances are removed from the covering surface and the back of the fleece before covering.
- ▶ Shear stress caused by trolleys, scaffolding or pulling heavy objects is not recommended and should be checked in advance if it is functional at all. This is particularly important in the overlap area.
- ▶ Observe the generally recognised rules of the trade and technology for floor covering and parquet installation, as well as the applicable national standards (e.g. EN, DIN, VOB, ÖNORM, SIA, etc.). The following standards and information sheets are also applicable or recommended for special attention.

COMPOSITION:

Polyester

PROTECTION OF THE WORKPLACE AND THE ENVIRONMENT:

The product itself does not require any special labour protection measures. Refer to the notes on protection of the workplace and the environment in the Product Information Sheets for the other installation materials used.

DISPOSAL:

All product residues are treated as normal construction waste.